

## Specialty Ladders

### Truck-N-Dock™ Ladders (50 degree)

- Designed with removable side and back chains for easy loading and unloading from any direction
- Large 36" x 48" top platform and 50 degree climbing angle are ideal for maximum efficiency
- Standard with our heavy duty G-strut tread for a 500 lb. capacity
- Front SAF-T Lock with 2½" diameter rubber pads are standard along with 10" semi-pneumatic rear wheels for rough surfaces

Step Width 36"					
Model No.	No. Steps	Platform Ht. (In.)	Overall Ht. (In.)	Base W x L (In.)	Wt. (Lbs.)
TD4R34L	4	40	73	46 x 81	228
TD5R34L	5	50	83	46 x 90	244
TD6R34L	6	60	93	46 x 99	260

May require special LTL carrier, Maximum height is 96" on most trailers.



TD4R34L Truck-N-Dock Ladder

### 50° Crossover Ladders

- Use as a stairway over conveyors or other obstacles
- For permanent or temporary installations
- Foot plates can be bolted to the floor for permanency
- Heavy duty, all-welded construction
- 24" wide steps in slip-resistant G-Strut tread or standard G-Perf tread
- Ships in one piece, already assembled

G-Strut Model No.	G-Perf Model No.	No. Steps	Clear Width (In.)	Clear Ht. (In.)	Overall Ht. (In.)	Overall Length (In.)
S4CR2C	P4CR2C	4	12	36	70	79
S4CR2D	P4CR2D	4	19	36	70	86
S4CR2E	P4CR2E	4	26	36	70	93
S4CR2F	P4CR2F	4	33	36	70	100
S4CR2G	P4CR2G	4	40	36	70	107
S5CR2C	P5CR2C	5	12	46	80	96
S5CR2D	P5CR2D	5	19	46	80	103
S5CR2E	P5CR2E	5	26	46	80	110
S5CR2F	P5CR2F	5	33	46	80	117
S5CR2G	P5CR2G	5	40	46	80	124
S6CR2C	P6CR2C	6	12	56	90	113
S6CR2D	P6CR2D	6	19	56	90	120
S6CR2E	P6CR2E	6	26	56	90	127
S6CR2F	P6CR2F	6	33	56	90	134
S6CR2G	P6CR2G	6	40	56	90	141



S5CR2C 50° Crossover Ladder